

The Drunken Sailor's Challenge

CS3630 Project 1

Due Beginning of Class 2 February 2006

Tucker Balch

January 24, 2006

1 Introduction

Ahhh, life in the Navy. It's not just a job, it's a robotics problem! You wake up to the sunrise after your last night of liberty in Singapore. You probably drank too much, but it was worth it. Anyhow, you find yourself amidst hundreds of cargo containers bound for Malaysia. Your watch reads seven forty-five. Uh oh, you've only got half an hour to reach your ship before it leaves port. Good thing that from here you can see the mast of your ship. Unfortunately, you still must negotiate the maze of cargo between here and there. Which brings us to the problem.

The challenge is for you to write an efficient C routine, `navigate()`, for navigation across a two dimensional field with obstacles. You will splice your function into the sailor's brain, `sailor.c`, and see if he makes it home. As input, your function will get a list of nearby obstacles, and an approximate heading to the ship. It should return a value indicating which way to go. Your function doesn't necessarily have to keep track of where the sailor is, the main program will do this. `main()` will repeatedly call your function and move the sailor in whatever direction you say until he reaches his ship.

If your function guides our sailor home, we can measure its efficiency in three ways:

1. **Path length:** how far did the sailor have to walk?
2. **Brain cells:** how large is your compiled function?
3. **Time:** how long did it take? Remember, it hurts to think with a hangover.

For grading, however, we will use path length only.

2 Nitty Gritties

Here are more details on the rules of the game:

For simplicity, this game takes place on a rectangular grid, so there are only a finite number of points the sailor can occupy. In fact, the grid is 23 by 80 cells, a convenient size for ASCII character animation. At each step, the sailor may move in any of eight compass directions: north, northeast, east, etc. (from here on out we'll abbreviate these with capital letters). Moves E, W, N or S cost 1 path unit, while diagonal moves (NE, SE, SW or NW) cost $\sqrt{2}$ units.

Each time your function, `navigate()`, is called it receives a list of nearby obstacles and the direction to the ship. The obstacle list is an array of nine integers set to `EMPTY`, `OCCUPIED`, or `GOAL` depending on whether or not a cargo container is blocking the way or the goal is adjacent to the sailor's position. Here is how the obstacle array is indexed:

NW	N	NE
W	SAILOR	E
SW	S	SE

These symbols have been defined for you in `sailor.h`, so the result of an expression like `if (obstacles[NW] == OCCUPIED)` would tell you if there is an obstacle to the NW of the sailor. The `SAILOR` element is always `EMPTY`. Note that if you ever command the sailor to move over an obstacle your command will be ignored. The direction to the ship is also given as one of the eight compass directions.

If you'd like to keep track of the sailor's location, you'll need to declare some static variables on your own.

3 Example Navigator

On to a concrete example. This `navigate()` function is automatically compiled with the distributed code. It uses a rather simple approach: first, it attempts to go towards the ship, but if that direction is blocked, it finds the next open direction.

```
#include "sailor.h"

int navigate(int obstacles[9], int ship_direction)
{
    int i;

    if (obstacles[ship_direction] == EMPTY)
        return(ship_direction);
    else
    {
```

}

you'll see the following picture on your screen:

[illegible]

and eventually reach the X. A trail of dots will trace the sailor's path.

the path to the left of the sailor, you'll find he gets trapped!

4 How to Get the Code

Get the code distribution

`http://orig.cc.gatech.edu/ipi/files/sailor.zip`. Unzip it with the command `unzip sailor.zip`. You should now have a directory called **sailor**. Under that you will find a **doc** subdirectory which contains this paper and a **src** directory which contains the code.

If you are on a Mac OS X box, you should be able to test the program by just typing `./demo src`. Otherwise you will need to recompile. To do that, move into the `src` directory and type `make sailor`. You will need the curses library and the gcc compiler. These are available on most Unix systems.

5 How to Test Your Algorithm

Just edit `src/navigate.c` to your satisfaction, then recompile with `make sailor`. You shouldn't have to do anything else (other than debug your code).

6 What to Turn In

You should email your (well commented) code (`navigate.c`) to Tucker (tucker@cc.gatech.edu). For evaluation purposes, all of your code should be contained within `navigate.c`. You can write your code on any platform you like, but it must compile and run on `thunderbird5.cc.gatech.edu` (a standard CoC linux box).

I will compile and test your code against the test problems distributed with the source code (look in the `test_problems`) subdirectory and against some of my own.

Additionally, at the beginning of class, you should submit a one to two page report that describes the algorithm you used. You should also characterize how well it works in different types of environments. If you use some method for estimating the location of the goal, be sure to explain how that works. Your source code should be stapled together with your report.

Your project will be evaluated on these criteria:

- Does your code compile? (40 points).
- Quality of write up (10 points).
- Completes test problem 1 (10 points).
- Completes test problem 2 (10 points).
- Completes test problem 3 (10 points).
- Completes test problem 4 (10 points).
- Does better than example code on 1-4 (0 to 10 points).

Regarding your writeup. Be sure to describe your algorithm sufficiently well that someone else could implement it. Analyze your algorithm, explaining its strengths and weaknesses. Extra credit points will be awarded if your algorithm is efficient, or elegant, or both.